

HP2100 Simulator Usage

30-Jan-2007

COPYRIGHT NOTICE

The following copyright notice applies to the SIMH source, binary, and documentation:

Original code published in 1993-2007, written by Robert M Supnik
Copyright (c) 1993-2007, Robert M Supnik

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL ROBERT M SUPNIK BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name of Robert M Supnik shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization from Robert M Supnik.

1	Simulator Files.....	3
2	HP2100 Features	3
2.1	CPU.....	4
2.2	12581A/12892B Memory Protect	7
2.3	12607B/12578A/12895A DMA Controllers, 12897B DCPC Controller	8
2.4	Variable Device Assignments.....	8
2.4.1	Device State	9
2.5	Programmed I/O Devices	9
2.5.1	12597A-002 Duplex Register Interface (PTR) with 2748 Paper Tape Reader... 9	
2.5.2	12597A-005 Duplex Register Interface (PTP) with 2895 Paper Tape Punch .. 10	
2.5.3	12531C Buffered Teleprinter Interface (TTY) with 2752 Teleprinter	11
2.5.4	12653A Printer Controller (LPS) with 2767 Line Printer, 12566B Microcircuit Interface with Loopback Connector	12
2.5.5	12845B Printer Controller (LPT) with 2607 Line Printer.....	13
2.5.6	12539C Time Base Generator (CLK)	14
2.5.7	12920A 16-Channel Terminal Multiplexer (MUX, MUXL, MUXM)	14
2.5.8	12875A Interprocessor Link (IPLI, IPLO).....	16
2.6	Disk Controllers	17
2.6.1	12557A Disk Controller (DPC, DPD) with Four 2781 Drives, 13210A Disk Controller (DPC, DPD) with Four 7900 Drives.....	17
2.6.2	12565A Disk Controller (DQC, DQD) with Two 2883 Drives	19
2.6.3	12606B Fixed Head Disk Controller (DRC, DRD) with 2770/2771 Disk, 12610B Drum Controller (DRC, DRD) with 2773/2774/2775 Drum	20
2.6.4	13037D Disk Controller (DS) with Eight 7905/7906/7920/7925 Drives	21
2.7	Magnetic Tape.....	23
2.7.1	12559C Magnetic Tape Controller (MTC, MTD) with One 3030 Drive.....	23
2.7.2	13181A Magnetic Tape Controller (MSC, MSD) with Four 7970B Drives, 13183A Magnetic Tape Controller (MSC, MSD) with Four 7970E Drives.....	24
3	Symbolic Display and Input	26

This memorandum documents the HP 2100 simulator.

1 Simulator Files

```
sim/          scp.h
              sim_console.h
              sim_defs.h
              sim_fio.h
              sim_rev.h
              sim_sock.h
              sim_tape.h
              sim_timer.h
              sim_tmxr.h
              scp.c
              sim_console.c
              sim_fio.c
              sim_sock.c
              sim_tape.c
              sim_timer.c
              sim_tmxr.c

sim/hp2100/  hp2100_cpu.h
              hp2100_cpu1.h
              hp2100_defs.h
              hp2100_fp.h
              hp2100_fp1.h
              hp2100_cpu.c
              hp2100_cpu0.c
              hp2100_cpu1.c
              hp2100_cpu2.c
              hp2100_cpu3.c
              hp2100_cpu4.c
              hp2100_fp.c
              hp2100_fp1.c
              hp2100_dp.c
              hp2100_dq.c
              hp2100_dr.c
              hp2100_ds.c
              hp2100_ipl.c
              hp2100_lps.c
              hp2100_lpt.c
              hp2100_mt.c
              hp2100_ms.c
              hp2100_mux.c
              hp2100_stddev.c
              hp2100_sys.c
```

2 HP2100 Features

The HP2100 simulator is configured as follows:

```
device names      simulates
```

CPU	2114C CPU with up to 16KW of memory 2115A CPU with up to 8KW of memory 2116C CPU with up to 32KW of memory 2100A CPU with up to 32KW of memory 1000 (21MX) M/E/F-Series CPU with up to 1024KW of memory EAU, FP, IOP, DMS, FFP, and/or DBI microcode extensions
MP	12581A/12892B memory protect
DMA0, DMA1	12607B/12578A/12895A direct memory access controller
DCPC0, DCPC1	12897B dual-channel port controller
PTR	12597A duplex register interface with 2748 paper tape reader
PTP	12597A duplex register interface with 2895 paper tape punch
TTY	12531C buffered teleprinter interface with 2752 teleprinter
LPS	12653A printer controller with 2767 line printer 12566B microcircuit interface with loopback connector
LPT	12845B printer controller with 2607 line printer
CLK	12539C time base generator
MUX, MUXL, MUXM	12920A 16-channel terminal multiplexer
DP	12557A disk controller with four 2871 drives 13210A disk controller with four 7900 drives
DQ	12565A disk controller with two 2883 drives
DR	12606B fixed head disk controller with 2770/2771 disk 12610B drum controller with 2773/2774/2775 drum
DS	13037D disk controller with eight 7905/7906/7920/7925 drives
MT	12559C magnetic tape controller with one 3030 drive
MS	13181A magnetic tape controller with four 7970B drives 13183A magnetic tape controller with four 7970E drives
IPLI	12875A interprocessor link, input side
IPL0	12875A interprocessor link, output side

The HP2100 simulator implements several unique stop conditions:

- Decode of an undefined instruction, and STOP_INST is set
- Reference to an undefined I/O device, and STOP_DEV is set
- More than INDMAX indirect references are detected during memory reference address decoding

The LOAD command supports standard absolute binary format. The DUMP command is not implemented.

2.1 CPU

CPU options include choice of model, memory size, and instruction sets. Several microcode options are simulated:

EAU	Extended Arithmetic Unit
FP	Single-Precision Floating Point
IOP	2000/Access I/O Processor
DMS	Dynamic Mapping System
FFP	Fast FORTRAN Processor
DBI	Double Integer Instructions

The following standard microcode is automatically enabled when the applicable 1000-Series CPU is selected:

EIG	Extended Instruction Group
FPP	Floating Point Processor
SIS	Scientific Instruction Set

The general command form is:

```
SET {-F} CPU <option>
```

Options that may be specified are:

SET CPU 2114	2114C CPU
SET CPU 2115	2115A CPU
SET CPU 2116	2116C CPU
SET CPU 2100	2100A CPU
SET CPU 1000-M	1000 M-Series CPU
SET CPU 1000-E	1000 E-Series CPU
SET CPU 1000-F	1000 F-Series CPU
SET CPU 21MX-M	21MX M-series CPU (same as 1000-M)
SET CPU 21MX-M	21MX E-series CPU (same as 1000-E)
SET CPU LOADERENABLE	enable device loader
SET CPU LOADERDISABLE	disable device loader
SET CPU EAU	EAU instructions
SET CPU NOEAU	no EAU instructions
SET CPU FP	FP instructions
SET CPU NOFP	no FP instructions
SET CPU IOP	IOP instructions
SET CPU NOIOP	no IOP instructions
SET CPU FFP	FFP instructions
SET CPU NOFFP	no FFP instructions
SET CPU DMS	DMS instructions
SET CPU NODMS	no DMS instructions
SET CPU DBI	Double Integer instructions
SET CPU NODBI	no Double Integer instructions
SET CPU 4K	set memory size = 4K
SET CPU 8K	set memory size = 8K
SET CPU 12K	set memory size = 12K
SET CPU 16K	set memory size = 16K
SET CPU 24K	set memory size = 24K
SET CPU 32K	set memory size = 32K
SET CPU 64K	set memory size = 64K
SET CPU 128K	set memory size = 128K
SET CPU 256K	set memory size = 256K
SET CPU 512K	set memory size = 512K
SET CPU 1024K	set memory size = 1024K

The CPU models and feature applicability are shown in the following table:

<u>Feature</u>	<u>2114C</u>	<u>2115A</u>	<u>2116C</u>	<u>2100A</u>	<u>1000M</u>	<u>1000E</u>	<u>1000F</u>
Max mem	16K	8K	32K	32K	1024K	1024K	1024K
MP	no	no	opt	std	opt	opt	opt
DMA	opt						
EAU	no	opt	opt	std	std	std	std
FP	no	no	no	opt	std	std	std
IOP	no	no	no	opt	opt	opt	opt

FFP	no	no	no	opt	opt	opt	std
EIG	no	no	no	no	std	std	std
DMS	no	no	no	no	opt	opt	opt
DBI	no	no	no	no	no*	opt	std
FFP/SIS	no	no	no	no	no	no	std

* DBI was not available for the 1000-M, but the simulator supports it for RTE-6/VM.

If a feature is standard for a given CPU, it cannot be disabled; if a feature is not included, it cannot be enabled.

On the 2100, the FP or FFP and IOP options are mutually exclusive. To support CPU detection in the HP diagnostic configurator, the 1000-E/F TIMER instruction decodes as MPY on the 1000-M, and the RRR 16 instruction decodes as NOP on the 2114. The 1000-F FFP supports several undocumented instructions used by the FPP-SIS-FFP diagnostic. All other disabled or unimplemented instructions cause a simulator halt if STOP_INST is set.

Setting the CPU model establishes a consistent set of standard features and common options. Additional SET CPU commands may follow to fine-tune the desired feature set.

The 2114, 2115, 2116, and 2100 models support a protected area of memory containing an initial binary loader. The loader always resides in the highest 64 memory locations, regardless of capacity. Enabling the loader makes this area available. Disabling the loader renders this area non-existent, so that reads from the area return zero, and writes to the area are ignored. The paper tape loader, configured for select code 10, initially resides in this area when the simulator is started.

The initial memory size is set to a maximum of 32K. If the memory size is being reduced, either by setting a smaller size or by changing to a CPU with a smaller memory capacity, and the memory being truncated contains non-zero data, the simulator asks for confirmation before proceeding. The confirmation request may be suppressed by using the "-f" switch. Data in the truncated portion of memory is lost.

These switches are recognized when examining or depositing in CPU memory:

```
-v          if DMS enabled, interpret address as virtual
-s          if DMS enabled, force system map
-u          if DMS enabled, force user map
-p          if DMS enabled, force port A map
-q          if DMS enabled, force port B map
```

The CPU implements four different kinds of instruction breakpoints:

```
-e          break unconditionally
-n          break if DMS is disabled
-s          break if DMS enabled and system map
-u          break if DMS enabled and user map
```

CPU registers include the visible state of the processor as well as the control registers for the interrupt system.

name	models	size	comments
P	all	15	program counter
A	all	16	A register
B	all	16	B register
M	all	15	M (memory address) register
T	all	16	T (memory data) register

X	1000	16	X index register
Y	1000	16	Y index register
S	all	16	switch/display register
E	all	1	extend flag
O	all	1	overflow flag
ION	all	1	interrupt enable flag
ION_DEFER	all	1	interrupt defer flag
CIR	all	6	central interrupt register
DMSENB	1000	1	DMS enable
DMSCUR	1000	1	DMS current map (1 = user map)
DMSSR	1000	16	DMS status register
DMSVR	1000	16	DMS violation register
DMSMAP[128]	1000	16	DMS maps [0:31] system map [32:63] user map [64:95] port A map [96:127] port B map
STOP_INST	all	1	stop on undefined instruction
STOP_DEV	all	1	stop on undefined device
INDMAX	all	16	indirect address limit
PCQ[0:63]	all	15	P of last JMP, JSB, or interrupt; most recent P change first

BOOT CPU implements the 1000 IBL facility. IBL is controlled by the switch register S. S<15:14> selects the device to boot:

00	2748B paper-tape reader (12992K ROM)
01	7900A/2883 disk (12992A ROM)
10	7970B/E tape (12992D ROM)
11	13037D disk (12992B ROM)

For the 7900A/2883 only, S<13:12> specify the type of disk:

00	7900A
10	2883

S<11:6> contains the device address. If the device has two addresses, S<11:6> specifies the lower address. S<5:3> are passed to the bootstrap program. S<2:0> specify options for the boot loader. IBL will not report an error if the device address in S<11:6> is incorrect.

2.2 12581A/12892B Memory Protect

Memory protect is standard equipment on the 2100 (although it may be disabled by removing a jumper) and optional on the 2116 and 1000. The following registers are implemented:

name	size	comments
CTL	1	memory protection enable
FLG	1	protection violation flag
FBF	1	protection violation flag buffer
FR	15	fence register
VR	16	violation register
EVR	1	enable violation register flag
MEV	1	memory expansion (DMS) violation flag

The 1000 memory protect card (12892B) has three feature options that are implemented by jumper settings. These are controlled by the following commands:

SET MP JSBIN	jumper W5 installed
SET MP JSBOUT	jumper W5 removed
SET MP INTIN	jumper W6 installed
SET MP INTOUT	jumper W6 removed
SET MP SEL1IN	jumper W7 installed
SET MP SEL1OUT	jumper W7 removed

W5 determines whether JSB instructions referencing memory locations 0 and 1 are legal (installed) or illegal (removed). W6 controls whether the first three levels of indirect addressing hold off (installed) or permit (removed) pending interrupts. W7 determines whether I/O instructions referencing select codes other than 1 are legal (installed) or illegal (removed); note that I/O instructions referencing select code 1 are legal, and HLT instructions are illegal, regardless of the setting of W7.

The default configuration is JSB (W5) installed, INT (W6) installed, and SEL1 (W7) removed, providing compatibility with the 2116 and 2100 memory protect cards.

2.3 12607B/12578A/12895A DMA Controllers, 12897B DCPC Controller

The direct memory access/dual channel port controller is an option for all CPUs. The 12607B DMA controller provides one channel, DMA0, on the 2114. The other DMA/DCPC controllers provide two channels (DMA0 and DMA1 on the 2115, 2116, and 2100, or DCPC0 and DCPC1 on the 1000). Each channel has the following visible state:

name	size	comments
CMD	1	channel enabled
CTL	1	interrupt enabled
FLG	1	channel ready
FBF	1	channel ready buffer
CTLALT	1	command word 2/3 selector
CW1	16	command word 1
CW2	16	command word 2
CW3	16	command word 3
LATENCY	8	first-cycle delay
BYTE	1	even/odd byte-packing flag
PACKER	8	byte-packing register

2.4 Variable Device Assignments

On the HP2100, I/O devices take their device numbers from the backplane slot they are plugged into. Thus, device number assignments vary considerably from system to system, and software package to software package. The HP2100 simulator supports dynamic device number assignment. To show the current device number, use the `SHOW <dev> DEVNO` command:

```
sim> SHOW PTR DEVNO
device=10
```

To change the device number, use the `SET <dev> DEVNO=<num>` command:

```
sim> SET PTR DEVNO=30
sim> SHOW PTR DEVNO
device=30
```

The new device number must be in the range 010..077 (octal). For devices with two device numbers, only the lower numbered device number can be changed; the higher is automatically set to the lower + 1. If a device number conflict occurs, the simulator will return an error when program execution is started.

2.4.1 Device State

All devices other than the CPU and TTY may be disabled or enabled. Disabling a device simulates removing the associated interface from the CPU card cage. To disable or enable a device, use:

```
SET <dev> DISABLED          disable device
SET <dev> ENABLED           enable device
```

For devices with more than one device number, disabling or enabling any device in the set disables or enables all of the devices.

Devices consisting of multiple addressable units connected to a controller typically allow the units to be individually enabled or disabled. Disabling simulates disconnecting the associated unit from the controller. The commands to set units enabled and disabled are:

```
SET <unit> DISABLED         disable unit
SET <unit> ENABLED          enable unit
```

Some devices and units allow simulation of power-down conditions. Power settings are controlled by these commands:

```
SET <dev> POWEROFF          turn power off
SET <dev> POWERON           turn power on
```

Peripherals that provide operator-selectable disconnection, typically via an "offline" switch, provide these simulation equivalents:

```
SET <dev> OFFLINE           set peripheral offline
SET <dev> ONLINE            set peripheral online
```

2.5 Programmed I/O Devices

2.5.1 12597A-002 Duplex Register Interface (PTR) with 2748 Paper Tape Reader

The paper tape reader (PTR) reads data from a disk file. The POS register specifies the number of the next data item to be read. Thus, by changing POS, the user can backspace or advance the reader.

For diagnostic purposes, a tape loop may be simulated with the commands:

```
SET PTR DIAG                rewind tape at EOF
SET PTR READER              supply tape trailer at EOF
```

The paper tape reader supports the `BOOT` command. `BOOT PTR` copies the IBL into memory and starts it running. The switch register (S) is set automatically to the value expected by the IBL loader:

```
<15:12> = 0000
<11:6>  = device code
<5:3>   = unchanged
```

<2:0> = 000

The paper tape reader implements these registers:

name	size	comments
BUF	8	last data item processed
CMD	1	reader enable
CTL	1	device/interrupt enable
FLG	1	device ready
FBF	1	device ready buffer
SRQ	1	device DMA service request
TRLLIM	8	number of trailing nulls to append after end-of-file is detected
POS	32	position in the input file
TIME	24	time from I/O initiation to interrupt
STOP_IOE	1	stop on I/O error

The TRLLIM register specifies the number of nulls to supply as paper tape trailer when EOF is detected. If TRLLIM is set to zero or the count is exhausted, the reader will hang.

Error handling is as follows:

error	STOP_IOE	processed as
not attached	1	report error and stop
	0	out of tape
end of file	1	report error and stop
	0	out of tape
OS I/O error	x	report error and stop

2.5.2 12597A-005 Duplex Register Interface (PTP) with 2895 Paper Tape Punch

The paper tape punch (PTP) writes data to a disk file. The POS register specifies the number of the next data item to be written. Thus, by changing POS, the user can backspace or advance the punch.

The paper tape punch implements these registers:

name	size	comments
BUF	8	last data item processed
CMD	1	punch enable
CTL	1	device/interrupt enable
FLG	1	device ready
FBF	1	device ready buffer
SRQ	1	device DMA service request
POS	32	position in the output file
TIME	24	time from I/O initiation to interrupt
STOP_IOE	1	stop on I/O error

Error handling is as follows:

error	STOP_IOE	processed as
not attached	1	report error and stop
	0	out of tape
OS I/O error	x	report error and stop

2.5.3 12531C Buffered Teleprinter Interface (TTY) with 2752 Teleprinter

The console teleprinter has three units: keyboard (unit 0), printer (unit 1), and punch (unit 2). The keyboard reads from the console keyboard; the printer writes to the simulator console window. The punch writes to a disk file. The keyboard and printer units (TTY0, TTY1) can be set to one of four modes: UC, 7P, 7B, or 8B:

mode	input characters	output characters
UC	lower case converted to upper case, high-order bit cleared	lower case converted to upper case, high-order bit cleared, non-printing characters suppressed
7P	high-order bit cleared	high-order bit cleared, non-printing characters suppressed
7B	high-order bit cleared	high-order bit cleared
8B	no changes	no changes

The default mode is UC.

Some HP software systems expect the console to transmit line-feed automatically following carriage-return. This feature is enabled with:

```
SET TTY AUTOLF
```

and disabled with:

```
SET TTY NOAUTOLF
```

The console teleprinter implements these registers:

name	size	comments
BUF	8	last data item processed
MODE	16	mode
CTL	1	device/interrupt enable
FLG	1	device ready
FBF	1	device ready buffer
SRQ	1	device DMA service request
KPOS	32	number of characters input
KTIME	24	keyboard polling interval
TPOS	32	number of characters printed
TTIME	24	time from I/O initiation to interrupt
PPOS	32	position in the punch output file
STOP_IOE	1	punch stop on I/O error

Error handling for the punch is as follows:

error	STOP_IOE	processed as
not attached	1	report error and stop

	0	out of tape
OS I/O error	x	report error and stop

2.5.4 12653A Printer Controller (LPS) with 2767 Line Printer, 12566B Microcircuit Interface with Loopback Connector

The 2767 line printer uses the 12653A line printer interface as its controller. As a line printer, LPS writes data to a disk file. The POS register specifies the number of the next data item to be written. Thus, by changing POS, the user can backspace or advance the printer.

The line printer responds to SET LPS POWEROFF as if the power were removed or the printer cable were disconnected, and to DETACH LPS as if the paper were out. It also provides these additional state commands:

SET LPS OFFLINE	simulate ONLINE button up
SET LPS ONLINE	simulate ONLINE button down
SET LPS REALTIME	use realistic timing for print operations
SET LPS FASTTIME	use optimized timing for print operations

As a 12566B microcircuit interface, LPS provides the test device for running several of the HP diagnostics. Printer mode versus diagnostic mode is controlled by the commands:

SET LPS PRINTER	configure as line printer
SET LPS DIAG	configure for diagnostic tests

In diagnostic mode, LPS simulates the installation of the HP 1251-0332 diagnostic test (loopback) connector onto the 12566B card and the setting of the appropriate card jumpers for the diagnostic.

LPS may be configured to send debugging information to the previously enabled debug output device using these commands:

SET LPS DEBUG	provide debug printouts
SET LPS NODEBUG	inhibit debug printouts

Diagnostic information includes characters supplied to and status received from the interface, as well as data transfer initiations and completions.

The 12653A is disabled by default.

The 12653A implements these registers:

name	size	comments
BUF	16	output buffer
STA	16	input buffer or status
POWER	2	printer power state
CMD	1	printer enable
CTL	1	device/interrupt enable
FLG	1	device ready
FBF	1	device ready buffer
SRQ	1	device DMA service request
CCNT	7	current character count
LCNT	7	current line count
POS	32	position in the output file

CTIME	24	character transfer time
PTIME	24	per-zone print operation time
STIME	24	per-line paper slew time
RTIME	24	power-on ready delay time
STOP_IOE	1	stop on I/O error

In printer mode, error handling is as follows:

error	STOP_IOE	processed as
not attached	1	report error and stop
	0	out of paper
SET POWEROFF	1	report error and stop
	0	powered off
SET OFFLINE	1	report error and stop
	0	offline
OS I/O error	x	report error and stop

With STOP_IOE set to 0, output performed when the device is powered off or offline will initiate but then hang, waiting for the device to be returned online. When it is, the output operation will complete.

In diagnostic mode, there are no errors; data sent to the output buffer is looped back to the status register immediately.

2.5.5 12845B Printer Controller (LPT) with 2607 Line Printer

The line printer (LPT) writes data to a disk file. The POS register specifies the number of the next data item to be written. Thus, by changing POS, the user can backspace or advance the printer.

The line printer responds to SET LPT POWEROFF as if the power were removed or the printer cable were disconnected and DETACH LPT as if the paper were out. It also provides these additional state commands:

SET LPT OFFLINE	simulate PAPER button up
SET LPT ONLINE	simulate PAPER button down

The line printer implements these registers:

name	size	comments
BUF	8	last data item processed
CMD	1	printer enable
CTL	1	device/interrupt enable
FLG	1	device ready
FBF	1	device ready buffer
SRQ	1	device DMA service request
LCNT	7	line count within page
POS	32	position in the output file
CTIME	24	time between characters
PTIME	24	time for a print operation
STOP_IOE	1	stop on I/O error

Error handling is as follows:

error	STOP_IOE	processed as
not attached	1	report error and stop
	0	out of paper
SET POWEROFF	1	report error and stop
	0	powered off
SET OFFLINE	1	report error and stop
	0	offline
OS I/O error	x	report error and stop

With STOP_IOE set to 0, output performed when the device is powered off or offline will initiate but then hang, waiting for the device to be returned online. When it is, the output operation will complete.

2.5.6 12539C Time Base Generator (CLK)

The time base generator (CLK) may be set for diagnostic mode:

SET CLK DIAG	configure for diagnostic mode
SET CLK CALIBRATED	configure for timing mode

Diagnostic mode corresponds to setting jumper W2 to position "B". This turns off autocalibration and divides the longest time intervals down by 1000.

The time base generator implements these registers:

name	size	comments
SEL	3	time base select
CTR	14	repeat counter for < 1Hz operation
CTL	1	device/interrupt enable
FLG	1	device ready
FBF	1	device ready buffer
ERR	1	error flag
TIME[0:7]	31	clock intervals, select = 0..7
DEVNO	6	current device number (read only)

The time base generator autocalibrates; the clock interval is adjusted up or down so that the clock tracks actual elapsed time. Operation at the fastest rates (100 microseconds, 1 millisecond) is not recommended.

2.5.7 12920A 16-Channel Terminal Multiplexer (MUX, MUXL, MUXM)

The 12920A is a 16-line terminal multiplexer, with five additional receive-only diagnostic lines. It consists of three devices:

MUX	scanning logic (corresponds to the upper data card)
MUXL	individual lines (corresponds to the lower data card)
MUXM	modem control and status logic (corresponds to the control card)

The MUX performs input and output through Telnet sessions connected to a user-specified port. The ATTACH command to the scanning logic specifies the port to be used:

```
ATTACH MUX <port>          set up listening port
```

where <port> is a decimal number between 1 and 65535 that is not being used for other TCP/IP activities.

Each line (each unit of MUXL) can be set to one of four modes: UC, 7P, 7B, or 8B:

mode	input characters	output characters
UC	lower case converted to upper case, high-order bit cleared	lower case converted to upper case, high-order bit cleared, non-printing characters suppressed
7P	high-order bit cleared	high-order bit cleared, non-printing characters suppressed
7B	high-order bit cleared	high-order bit cleared
8B	no changes	no changes

In addition, each line supports the DATASET option. DATASET, when set, enables modem control. The default settings are UC mode and DATASET disabled. Finally, each line supports output logging. The SET MUXLn LOG command enables logging on a line:

```
SET MUXLn LOG=filename  log output of line n to filename
```

The SET MUXLn NOLOG command disables logging and closes the open log file, if any.

The modem controls model a simplified Bell 103A dataset with just four lines: data terminal ready and request to send from the computer to the data set, and carrier detect and data set ready from the data set to the computer. There is no ring detection. If data terminal ready is set when a Telnet connection starts up, then carrier detect and data set ready are also set. The connection is established whether data terminal ready is set or not.

Once MUX is attached and the simulator is running, the multiplexer listens for connections on the specified port. It assumes that the incoming connections are Telnet connections. The connections remain open until disconnected either by the Telnet client, a SET MUXL DISCONNECT command, or a DETACH MUX command.

Other special multiplexer commands:

SHOW MUX CONNECTIONS	show current connections
SHOW MUX STATISTICS	show statistics for active connections
SET MUXLn DISCONNECT	disconnects the specified line.

The scanner (MUX) implements these registers:

name	size	comments
IBUF	16	input buffer, holds line status
OBUF	16	output buffer, holds channel select

The lines (MUXL) implements these registers:

name	size	comments
CTL	1	device/interrupt enable
FLG	1	device ready
FBF	1	device ready buffer
SRQ	1	device DMA service request

STA[0:20]	16	line status, lines 0-20
RPAR[0:20]	16	receive parameters, lines 0-20
XPAR[0:15]	16	transmit parameters, lines 0-15
RBUF[0:20]	8	receive buffer, lines 0-20
XBUF[0:15]	8	transmit buffer, lines 0-15
RCHP[0:20]	1	receive character present, lines 0-20
XDON[0:15]	1	transmit done, lines 0-15
TIME[0:15]	24	transmit time, lines 0-15

The modem control (MUXM) implements these registers:

name	size	comments
CTL	1	device/interrupt enable
FLG	1	device ready
FBF	1	device ready buffer
SRQ	1	device DMA service request
SCAN	1	scan enabled
CHAN	4	current line
DSO[0:15]	6	C2,C1,ES2,ES1,SS2,SS1, lines 0-15
DSI[0:15]	2	S2,S1, lines 0-15

The terminal multiplexer does not support save and restore. All open connections are lost when the simulator shuts down or MUX is detached.

2.5.8 12875A Interprocessor Link (IPLI, IPLO)

The interprocessor link is a pair of 12566B parallel interfaces that are cross-coupled to provide interprocessor communications to a second copy of the HP2100 simulator. The IPL is intended to support simulation of a two-system HP TimeShared Basic configuration. The links are actually bidirectional half-duplex; TimeShared Basic uses them unidirectionally. The IPL is disabled by default.

To operate, the IPL devices must be enabled and then connected to the IPL devices in another copy of the simulator. The IPLI device in the first simulator is connected to the IPLO device in the second, and vice versa. Connections are established with the ATTACH command. One copy of the simulator listens for connections on a specified port (ATTACH -L); the other establishes connections to an IP address and port (ATTACH -C). Either copy may perform either operation, but the operations must be done in matched pairs:

```

simulator #1                                simulator #2

sim> set ipli ena                             sim> set ipli ena
(also enables iplo)                          (also enables iplo)
sim> att -lw ipli 4000                        sim> att -c iplo 4000
Listening on port 4000                        Connected to 127.0.0.1 port 4000
Waiting for connection

Connection established                         sim> att -c ipli 4001
sim> att -lw iplo 4001                        Connected to 127.0.0.1 port 4000
Listening on port 4001
Waiting for connection

```

Both forms of ATTACH take a modifier -W (wait); if specified, the command will wait up to 30 seconds for the connection process to complete. ATTACH -C can specify both an IP address and a port, in the form aa.bb.cc.dd:port; if the IP address is omitted, it defaults to 127.0.0.1 (local system).

Both IPLI and IPLO implement the `BOOT` command. `BOOT` loads the HP Access Basic Block Loader for the IOP into the top 64 words of memory and starts it running.

Both IPLI and IPLO implement these registers:

name	size	comments
BUF	16	buffer
HOLD	8	holding buffer
CMD	1	device enable
CTL	1	device/interrupt enable
FLG	1	device ready
FBF	1	device ready buffer
SRQ	1	device DMA service request
TIME	24	polling interval for input
STOP_IOE	1	stop on I/O error

2.6 Disk Controllers

2.6.1 12557A Disk Controller (DPC, DPD) with Four 2781 Drives, 13210A Disk Controller (DPC, DPD) with Four 7900 Drives

The 12557A/13210A disk controller has two separate devices, a data channel (DPD) and a command channel (DPC). The data channel includes a 128-word (one sector) buffer for reads and writes. The command channel includes the four disk drives. The 12557A/13210A controller can be configured as either a 12557A, supporting 2.5MB drives, or a 13210A, supporting 5MB drives, with the commands:

```
SET DPC 12557A          2.5MB drives
SET DPC 13210A          5.0MB drives
```

Drive types cannot be intermixed; the controller is configured for one type or the other. The 13210A (for 7900/7901 disks) is selected by default.

Individual drives may be protected against writing. These commands simulate the Upper/Lower Disc Protect switches on the drives:

```
SET DPCn LOCKED          set unit n write locked
SET DPCn WRITEENABLED    set unit n write enabled
```

Separate protection for the upper and lower platters of the 7900 drive is not supported. Also, the drive Protect/Override switch is not supported; drive protection is permanently overridden.

Drives may also have their heads unloaded and loaded:

```
SET DPCn UNLOADED        unload heads on unit n
SET DPCn LOADED          load heads on unit n
```

This provides a convenient method of setting a drive "down" without detaching the associated disk image file. Drives can also be set `DISABLED` or `ENABLED`.

The 12557A/13210A supports the `BOOT` command. `BOOT DPC` copies the IBL for 7900 class disks into memory and starts it running. `BOOT -R DPC` boots from the removable platter (head 0). The switch register (S) is set automatically to the value expected by the IBL loader:

```

<15:14>    =    01
<13:12>    =    00
<11:6>     =    data channel device code
<5:3>      =    unchanged
<2:1>      =    00
<0>        =    1 if booting from the removable platter

```

The data channel (DPD) implements these registers:

name	size	comments
IBUF	16	input buffer
OBUF	16	output buffer
DBUF[0:127]	16	sector buffer
BPTR	7	sector buffer pointer
CMD	1	channel enable
CTL	1	interrupt enable
FLG	1	channel ready
FBF	1	channel ready buffer
SRQ	1	channel DMA service request
XFER	1	transfer in progress flag
WVAL	1	write data valid flag

The command channel (DPC) implements these registers:

name	size	comments
OBUF	16	output buffer
BUSY	4	busy (unit #, + 1, of active unit)
CNT	5	check record count
CMD	1	controller enable
CTL	1	interrupt enable
FLG	1	controller ready
FBF	1	controller ready buffer
SRQ	1	controller DMA service request
EOC	1	end of cylinder pending
POLL	1	attention polling enabled
RARC	8	record address register (cylinder)
RARH	2	record address register (head)
RARS	4	record address register (sector)
CYL[0:3]	8	current cylinder, drives 0-3
STA[0:3]	16	drive status, drives 0-3
CTIME	24	data transfer command delay time
DTIME	24	data channel command delay time
STIME	24	seek delay time, per cylinder
XTIME	24	interword transfer time

Error handling is as follows:

```

error                processed as
not attached         disk not ready (heads unloaded)

```

```

end of file          assume rest of disk is zero

OS I/O error        report error and stop

```

2.6.2 12565A Disk Controller (DQC, DQD) with Two 2883 Drives

The 12565A disk controller has two separate devices, a data channel (DQD) and a command channel (DQC). The data channel includes a 128-word (one sector) buffer for reads and writes. The command channel includes the two disk drives.

Individual drives may be protected against writing:

```

SET DQcN LOCKED          set unit n write locked
SET DQcN WRITEENABLED   set unit n write enabled

```

Drives may have their heads unloaded and loaded:

```

SET DQcN UNLOADED       unload heads on unit n
SET DQcN LOADED         load heads on unit n

```

This provides a convenient method of setting a drive "down" without detaching the associated disk image file. Disk drives can also be set `DISABLED` or `ENABLED`.

The 12565A supports the `BOOT` command. `BOOT DQC` copies the IBL for 2883 class disks into memory and starts it running. The switch register (S) is set automatically to the value expected by the IBL loader:

```

<15:12>    =    0110
<11:6>     =    data channel device code
<5:3>      =    unchanged
<2:0>      =    000

```

The data channel (DQD) implements these registers:

name	size	comments
IBUF	16	input buffer
OBUF	16	output buffer
DBUF[0:127]	16	sector buffer
BPTR	7	sector buffer pointer
CMD	1	channel enable
CTL	1	interrupt enable
FLG	1	channel ready
FBF	1	channel ready buffer
SRQ	1	channel DMA service request
XFER	1	transfer in progress flag
WVAL	1	write data valid flag

The command channel (DQC) implements these registers:

name	size	comments
OBUF	16	output buffer
BUSY	2	busy (unit # + 1 of active unit)
CNT	9	check record count
CMD	1	controller enable

CTL	1	interrupt enable
FLG	1	controller ready
FBF	1	controller ready buffer
SRQ	1	controller DMA service request
RARC	8	record address register (cylinder)
RARH	5	record address register (head)
RARS	5	record address register (sector)
CYL[0:1]	8	current cylinder, drives 0-1
HED[0:1]	5	current head, drives 0-1
STA[0:1]	16	drive status, drives 0-1
CTIME	24	data transfer command delay time
DTIME	24	data channel command delay time
STIME	24	seek delay time, per cylinder
XTIME	24	interword transfer time

Error handling is as follows:

error	processed as
not attached	disk not ready (heads unloaded)
end of file	assume rest of disk is zero
OS I/O error	report error and stop

2.6.3 12606B Fixed Head Disk Controller (DRC, DRD) with 2770/2771 Disk, 12610B Drum Controller (DRC, DRD) with 2773/2774/2775 Drum

The 12606B/12610B fixed head disk/drum controller has two separate devices, a data channel (DRD) and a command channel (DRC). The command channel includes the actual drive. Ten different models are supported:

command	interface and size	model
SET DRC 180K	12606B, 180K words	2770A
SET DRC 360K	12606B, 360K words	2771A
SET DRC 720K	12606B, 720K words	2771A-001
SET DRC 384K	12610B, 384K words	2773A
SET DRC 512K	12610B, 512K words	2773A-001
SET DRC 640K	12610B, 640K words	2773A-002
SET DRC 768K	12610B, 768K words	2774A
SET DRC 896K	12610B, 896K words	2774A-001
SET DRC 1024K	12610B, 1024K words	2774A-002
SET DRC 1536K	12610B, 1536K words	2775A

The command channel supports write-protected tracks. Track protection is enabled with this command:

```
SET DRC PROTECTED
```

In addition, the number of protected tracks is specified by the command:

```
SET DRC TRACKPROT=count
```

The track protect count must be a power of two from 1 to 128 on the 12606 interface and from 1 to 512, or 768, on the 12610 interface. If the drive has fewer tracks than the track protect count, then all tracks on the drive are eligible for protection.

Track protection is disabled with this command:

```
SET DRC UNPROTECTED
```

The 12606B/12610B support the `BOOT` command. `BOOT DRD` loads the first sector from the disk or drum into locations 0-77 and then jumps to 77. This is very different from the IBL loader protocol used by the 12565A and the 12557A/13210A.

The data channel (DRD) implements these registers:

name	size	comments
IBUF	16	input buffer
OBUF	16	output buffer
CMD	1	channel enable
CTL	1	interrupt enable
FLG	1	channel ready
FBF	1	channel ready buffer
SRQ	1	channel DMA service request
BPTR	6	sector buffer pointer

The command channel implements these registers:

name	size	comments
CW	16	command word
STA	16	status
RUN	1	run flip-flop
CMD	1	controller enable
CTL	1	interrupt enable
FLG	1	controller ready
FBF	1	controller ready buffer
SRQ	1	controller DMA service request
TIME	24	interword transfer time
STOP_IOE	1	stop on I/O error

Error handling is as follows:

error	processed as
not attached	drum or disk not ready

12606B/12610B data files are buffered in memory; therefore, end of file and OS I/O errors cannot occur.

2.6.4 13037D Disk Controller (DS) with Eight 7905/7906/7920/7925 Drives

The 13037D disk controller supports 7905 (15MB), 7906 (20MB), 7920 (50MB), or 7925 (120MB) disk drives, as well as autosizing, based on the size of the disk image file:

```
SET DSn 7905      drive n is a 15MB drive
SET DSn 7906      drive n is a 20MB drive
SET DSn 7920      drive n is a 50MB drive
```

```

SET DSn 7925           drive n is a 120MB drive
SET DSn AUTOSIZE       drive n type based on file size at ATTACH

```

Drive types can be intermixed. The 7905 is selected by default.

Individual drives may be protected against writing. These commands simulate the Disc Protect/Read Only switches on the drives:

```

SET DSn LOCKED         set unit n write locked
SET DSn WRITEENABLED   set unit n write enabled

```

Separate protection for the upper and lower platters of the 7905 and 7906 drives is not supported. Protecting a 7905 or 7906 drive behaves as though both of the Disc Protect switches were on.

Drives may also have their heads unloaded and loaded:

```

SET DSn UNLOADED       unload heads on unit n
SET DSn LOADED         load heads on unit n

```

This provides a convenient method of setting a drive "down" without detaching the associated disk image file.

The setting of the drive Format switch may be changed with:

```

SET DSn FORMAT         set format enabled
SET DSn NOFORMAT       set format disabled

```

Drives can also be set DISABLED or ENABLED.

The 13037D supports the `BOOT` command. `BOOT DS` copies the IBL loader for the 13037D controller into memory and starts it running. The switch register (S) is set automatically to the value expected by the IBL loader:

```

<15:14> = 11
<13:12> = 01
<11:6>  = data channel device code
<5:3>   = unchanged
<2>     = 0
<1:0>   = unchanged (head number)

```

The DS controller implements these registers:

name	size	comments
CMD	16	command register
FIFO[0:15]	16	data FIFO
SR1	16	status register 1
VCTR	16	verify counter
FMASK	8	file mask
CYL	16	cylinder address register
HS	16	head/sector address register
STATE	2	controller state
LASTA	3	last unit polled for attention flag
FIP	4	FIFO insertion pointer
FRP	4	FIFO removal pointer
FCNT	5	FIFO counter

CTL	1	interrupt enable
FLG	1	ready flag
FBF	1	ready flag buffer
SRQ	1	DMA service request
BUSY	1	visible busy status
CMDP	1	command follows flag
CMDP	1	command pending flag
EOC	1	end of cylinder flag
EOD	1	end of data flag
DBUF [0:127]	16	sector buffer
DPTR	8	sector buffer pointer
CTIME	24	command response time
DTIME	24	data transfer response time
STIME	24	seek time (per cylinder)
RTIME	24	rotation time
TIMEOUT	31	controller timeout

Error handling is as follows:

error	processed as
not attached	disk not ready (heads unloaded)
end of file	assume rest of disk is zero
OS I/O error	report error and stop

2.7 Magnetic Tape

2.7.1 12559C Magnetic Tape Controller (MTC, MTD) with One 3030 Drive

The 12559C magnetic tape drive has two separate devices, a data channel (MTD) and a command channel (MTC). The data channel includes a maximum record sized buffer for reads and writes. The command channel includes the tape unit. Magnetic tape options include the ability to make the unit write enabled or write locked.

SET MTC LOCKED	set unit write locked
SET MTC WRITEENABLED	set unit write enabled

The `BOOT` command is not supported. The 12559C was HP's earliest tape drive and is not supported by most of its operating systems. It is disabled by default.

The data channel (MTD) implements these registers:

name	size	comments
FLG	1	channel ready
SRQ	1	channel DMA service request
DBUF [0:65535]	8	transfer buffer
BPTR	16	buffer pointer (reads and writes)
BMAX	16	buffer size (writes)

The command channel (MTC) implements these registers:

name	size	comments
------	------	----------

FNC	8	current function
STA	9	tape status
BUF	8	buffer
CTL	1	interrupt enabled
FLG	1	controller ready
FBF	1	controller ready buffer
SRQ	1	controller DMA service request
DTF	1	data transfer flop
FSVC	1	first service flop
POS	32	magtape position
CTIME	24	command delay time
XTIME	24	interword transfer delay time
STOP_IOE	1	stop on I/O error

Error handling is as follows:

error	processed as
not attached	tape not ready; if STOP_IOE, stop
end of file	parity error
OS I/O error	parity error; if STOP_IOE, stop

2.7.2 13181A Magnetic Tape Controller (MSC, MSD) with Four 7970B Drives, 13183A Magnetic Tape Controller (MSC, MSD) with Four 7970E Drives

The 13181A/13183A magnetic tape drive has two separate devices, a data channel (MTD) and a command channel (MTC). The data channel includes a maximum record sized buffer for reads and writes. The command channel includes the tape units. Magnetic tape options include the ability to select the 13181A (800 bpi) controller or the 13183A (1600 bpi) controller, and the ability to set a drive offline and online, write enabled or write locked.

SET MSC 13181A	set controller to 13181A
SET MSC 13183A	set controller to 13183A
SET MSCn OFFLINE	set unit n offline
SET MSCn ONLINE	set unit n online
SET MSCn LOCKED	set unit n write locked
SET MSCn WRITEENABLED	set unit n write enabled
SET MSC REALTIME	set controller to actual timing
SET MSC FASTTIME	set controller to optimized timing (default)
SET MSCn REEL=length	set unit tape reel size
	0 = unlimited (default)
	600 = 600 feet
	1200 = 1200 feet
	2400 = 2400 feet
SET MSCn CAPAC=m	set unit n capacity to m MB (0 = unlimited)

Setting the controller to optimized timing with SET MSC FASTTIME also enables two other optimizations: the initial gap normally written after BOT is omitted, and the Gap and File Mark (GFM) command is executed as a Write File Mark (WFM) command instead. Note that this does not affect the Write Gap (GAP) command.

MSC may be configured to send debugging information to the previously enabled debug output device using these commands:

```

SET MSC DEBUG           provide debug printouts
SET MSC NODEBUG        inhibit debug printouts

```

Three debug flags that control the reporting level are supported:

```

CMDS          Report command initiations and completions
CPU           Report words received from and sent to the CPU
RWS          Report tape library reads, writes, and status returns

```

The 13181A/13183A supports the `BOOT` command. `BOOT MSC` loads the IBL for 7970B/E magnetic tape drives into memory and starts it running. `BOOT -S MSC` causes the loader to position to the file number specified in the A register before starting to load data. The switch register (S) is set automatically to the value expected by the IBL loader:

```

<15:12>      =      1000
<11:6>       =      data channel device code
<5:3>        =      unchanged
<2:0>        =      00
<0>          =      1 if position tape before loading

```

The data channel (MSD) implements these registers:

name	size	comments
BUF	16	data buffer
CTL	1	interrupt enabled
FLG	1	channel ready
FBF	1	channel ready buffer
SRQ	1	channel DMA service request
DBUF[0:65535]	8	transfer buffer
BPTR	17	buffer pointer (reads and writes)
BMAX	17	buffer size (writes)

The command channel (MSC) implements these registers:

name	size	comments
STA	12	tape status
BUF	16	buffer
USEL	2	currently selected unit
FSVC	1	first service flop
CTL	1	interrupt enabled
FLG	1	controller ready
FBF	1	controller ready buffer
SRQ	1	controller DMA service request
POS[0:3]	32	magtape position
BTIME	24	BOT start delay time
CTIME	24	command delay time
GTIME	24	gap traversal time
ITIME	24	IRG traversal time
RTIME	24	rewind initiation time
XTIME	24	interword transfer delay time
STOP_IOE	1	stop on I/O error

Error handling is as follows:

error	processed as
not attached	tape not ready; if STOP_IOE, stop
end of file	parity error
OS I/O error	parity error; if STOP_IOE, stop

3 Symbolic Display and Input

The HP2100 simulator implements symbolic display and input. Display is controlled by command line switches:

-a	display as ASCII character
-c	display as two packed ASCII characters
-m	display instruction mnemonics

Input parsing is controlled by the first character typed in or by command line switches:

' or -a	ASCII character
" or -c	two packed ASCII characters
alphabetic	instruction mnemonic
numeric	octal number

Instruction input uses standard HP2100 assembler syntax. There are seven instruction classes: memory reference, I/O, shift, alter skip, extended shift, extended memory reference, extended two address reference.

Memory reference instructions have the format

```
memref {C/Z} address{,I}
```

where I signifies indirect, C a current page reference, and Z a zero page reference. The address is an octal number in the range 0 - 077777; if C or Z is specified, the address is a page offset in the range 0 - 01777. Normally, C is not needed; the simulator figures out from the address what mode to use. However, when referencing memory outside the CPU (e.g., disks), there is no valid PC, and C must be used to specify current page addressing.

I/O instructions have the format

```
io device{,C}
```

where C signifies that the device flag is to be cleared. The device is an octal number in the range 0 - 77.

Shift and alter/skip instructions have the format

```
sub-op sub-op sub-op...
```

The simulator checks that the combination of sub-opcodes is legal.

Extended shift instructions have the format

extshift count

where count is an octal number in the range 1 - 020.

Extended memory reference instructions have the format

extmemref address{,I}

where I signifies indirect addressing. The address is an octal number in the range 0 - 077777.

Extended two address instructions have the format

ext2addr addr1{,I},addr2{,I}

where I signifies indirect addressing. Both address 1 and address 2 are octal numbers in the range 0 - 077777.